


TENDER DOCUMENT
FOR
SUPPLY OF STAINLESS STEEL HOSES AND
BELLOWS
FOR CRUDE OIL APPLICATION
AT
REFINERIES & OIL INSTALLATIONS
PRICED BID – PART – II

Tender No.: ROFS/2K/06/ENQ/05

Tender Date : 22.02.2021

Due Date : 04.03.2021 UPTO 16:00 HOURS



Balmer Lawrie & Co. Ltd.
REFINERY & OILFIELD SERVICES
21, Netaji Subhas Road
Kolkata 700 001



Balmer Lawrie & Co. Ltd.
Refinery & Oilfields Services
PRICE BID

Sl. No.	Description	Qty. (No.)	Rate (₹)	Amount (₹)
1.0	SUPPLY OF SS HOSES AND BELOWS			
1.1	3" dia x 2m in length SS316L Corrugated Flexible Hose Reinforced steel double helix crossing antistatic wires suitable for working pressure of 16 Kg/cm ² (g) at 80°C max. temp. fitted with 4" dia groove at one end and 3" dia MS Flange as per ASA 150 at other end	7		
1.2	4" dia x 3m in length SS316L Corrugated Flexible Hose Reinforced steel double helix crossing antistatic wires suitable for working pressure of 16 Kg/cm ² (g) at 80°C max. temp. fitted 4" dia MS Flange as per ASA 150 at one end and 4" dia groove at other end	7		
1.3	4" dia x 2m in length SS316L Corrugated Flexible Hose Reinforced steel double helix crossing antistatic wires suitable for working pressure of 16 Kg/cm ² (g) at 80°C max. temp. fitted with 4" dia groove at both ends	12		
1.4	4" dia x 3m in length SS316L Corrugated Flexible Hose Reinforced steel double helix crossing antistatic wires suitable for working pressure of 16 Kg/cm ² (g) at 80°C max. temp. fitted with 4" dia MS Flange as per ASA 150 at both ends	7		
1.5	6" dia x 2m in length SS 316L Corrugated Flexible Hose Reinforced steel double helix crossing antistatic wires suitable for steam of working pressure 16Kg/cm ² (g) at 80°C max. temp. fitted with 6" dia groove at one end and 6" dia MS Flange as per ASA 150 at other end	2		
1.6	6" dia x 3m in length SS 316L Corrugated Flexible Hose Reinforced steel double helix crossing antistatic wires suitable for steam of working pressure 16Kg/cm ² (g) at 80°C max. temp. fitted with 6" dia groove at one end and 6" dia MS Flange as per ASA 150 at other end	2		
1.7	2" dia x 2m in length SS 316L Corrugated Flexible Hose Reinforced steel double helix crossing antistatic wires suitable for steam of working pressure 16Kg/cm ² (g) at 80°C max. temp. fitted with 2" dia MS Flange as per ASA 150 at both ends.	10		
1.8	6" dia x 19 cm in length (flange to flange) flexible SS Below fitted with 6" dia MS Flange (Swivel) as per ASA 150	2		
1.9	4" dia x 19 cm in length (flange to flange) flexible SS Below fitted with 4" dia MS Flange (Swivel) as per ASA 150	2		
2.0	Basic Price			
3.0	Packing & Forwarding			
4.0	Freight Charges upto CPCL, Manali Refinery, Chennai			
5.0	Total (without GST)			
6.0	Goods & Services Tax @			
7.0	Landed Cost			